

FusionSolar 8.0 Smart PV Solution



SUN2000-330KTL-H2



01

PV technology evolution and trends

Inverter Roadmap and Evolution: Functional Machines to Smart Machines



Inverter Architecture Evolution



Central
INV



SUN2000-V1.1

- Number of input strings: 6
- AC voltage: 380/400 V AC
- Rated power: 8–20 kW

- Number of input strings: 6
- AC voltage: 480 V AC
- Rated power: 30–36 kW



SUN2000-V2.2
SUN2000HA-V1.1

1100 V input

- Number of input strings: 8
- AC voltage: 500 V AC
- Rated power: 50 kW

1500 V input

- Number of input strings: 8
- AC voltage: 800 V AC
- Rated power: 60 kW



SUN2000-V3.1
SUN2000HA-V2.1

- Number of input strings: 12
- AC voltage: 800 V AC
- Rated power: 70 kW

1500 V input

- Number of input strings: 12
- AC voltage: 800 V AC
- Rated power: 100 kW



SUN2000HA-V3.1
SUN2000-V5.1

1100 V input

- Number of input strings: 20
- AC voltage: 380 V AC/500 V AC
- Rated power: 100 kW/136 kW

1500 V input


- Number of input strings: 18
- AC voltage: 800 V AC
- Rated power: 185 kW



HAV5 (MPPT+INV)

+1500V input, 330KTL

- Number of input strings: 28
- AC voltage: 800 V AC
- Rated power: 330 kW



➤ The development of all science and technology routes follows the direction of system efficiency improvement and cost reduction.

Global R&D teams and technology platforms: Leveraging the domain specific advantages globally to keep leading



6000+ employees
60% R&D




12 R&D centers



10%+ R&D investment



1300+ patents



Smart PV: All-scenario PV & storage solution, accelerating the shift to zero carbon generation

PV & storage Utility solution

Challenges: High PV LCOE and weak grid problem

Trend: PV & storage coordinated solution, creating the smart PV generator and accelerating the shift to zero carbon generation

C&I solution

Challenges: High electricity cost and low system safety

Trend: Green C&I power solution with integrated PV & storage architecture, entering thousands of C&I fields and adapting to different scenarios

Residential solution

Challenges: High safety risks and low system safety

Trend: "1+3+X" architecture, increasing the self-consumption ratio and reducing the electricity cost

Microgrid solution

Challenges: High diesel generators cost and pollution

Trend: Comprehensive off-grid fuel removal PV & storage solution, helping bridge the energy divide

Utility-scale PV plant



The largest single-site PV project, Qinghai, 2.2 GW

Commercial & industrial PV rooftop



Longyang road metro station PV project, Shanghai, 3.66MW

Residential PV rooftop



Family green power PV & ESS project, Dongguan, 30kW


Island off-grid PV power station



Maritime bureau PV & off-grid energy supply project, Zhuhai, 24kW


Renewable energy penetration rate increases, power grid declines, and requirements for power grid friendliness increase rapidly

In the next five years, half of global power grids will be declining.



The power grid declines rapidly, and the stability problem becomes more and more serious.


The requirement for power grid friendliness is rapidly increased.



02

Introduction of Huawei PV Solution

FusionSolar : Higher Yields, Safe and Reliable, Smart O&M, and Grid Forming



Higher Yields

- Perfectly match high-current modules, especially 210mm
- Smart SDS, yields increased by 1%

Smart O&M

- Smart I-V Diagnosis 4.0
- Smart PV & ESS management system

Safe and Reliable

- DC safety: Smart string level disconnector
- IP66 fully sealed


Grid Forming

- Full power operation even SCR low to 1.1 (full output)
- THDi \leq 1%, SCCR supported to 0.7

US\$0.031-0.046/kWh


Industrial-leading Dynamic MPPT Efficiency

Better Ability to Capture Max. Power Point in Actual Operation




Smart string level disconnector: Precise fault detection, rapidly disconnect DC system faults

Smart String-Level Disconnector



15ms Automatic Disconnect



Success Case



CSI Brazil
100MW






Solaria Spain
50MW



Hebei China
50MW

AI BOOST Optimizes Tracker Control Tracking Algorithm



Tracker Type	Flat single axis tracker
Data Analysis	Control and calculation based on power value of PV strings collected by smart string inverters
Comm. Solution	Tracker controller connected to the inverter via RS485) Tracker controller ->RS485-> inverter -> SmartLogger.
Quantity Limitation	Quantity of controller supported by a single inverter ≤16
Cooperated vendors	  

Smart IV Curve Diagnosis 4.0: Online and Full diagnosis, Reducing O&M Costs

Recall ratio, consistency, accuracy >95%

L4 Highest Level in the Industry

Level	Exception identification		Fault Diagnosis
	Recall rate ¹	Recurrence rate ²	accuracy ³
L1	≥75%	≥70%	≥70%
L2	≥85%	≥80%	≥80%
L3	≥90%	≥85%	≥85%
L4	≥95%	≥90%	≥90%
Result	100%	96.23%	96.8%

Worldwide Application **>15GW**, improving O&M efficiency

Project: XX Rooftop PV Plant, Ningbo, Zhejiang



528 Total String
62 Faulty String
11.7% Failure Rate

Project: XX PV Plant, Yangquan, Shanxi



3960 Total String
188 Faulty String
4.7% Failure Rate

Smart IV Curve Diagnosis

Better adaptability

- large-scale ground & mountain scenarios ;
- Compatible with mainstream components such as half-chip, tile, 166, 182, and 210

Loss assessment

- Quantifying the power generation loss of a faulty string
- Plant O&M Guide

Scheduled scanning

- Periodic diagnosis and email results for a good experience

Integrated by ISVs

- Open API (Restful)
- Integrated by ISVs (2021Q4)

Fine-grained data

- The inverter automatically obtains radiation.
- String-level parameter configuration

Higher availability

- overview report, diagnosis curve report, and fault O&M report.
- Provide raw data for customer self-development.

Smart I-V Curve Diagnosis 4.0: Online and Full diagnosis, Reducing O&M Costs

Traditional I-V Testing VS Smart I-V Curve Diagnosis

	Traditional I-V Testing	Huawei Smart I-V Curve Diagnosis
Tools Cost	Four sets of instruments & Software \$46,200	Only Software
Time(300MW Inspection)	30 Days	30 Minutes
Yields Loss	Inverter Off When Testing \$4,886	Almost Zero
Labor Cost	12 Professionals \$24,000	No professionals required, just O&M staff is sufficient
Total	\$75,086	-

I-V Test for Twice per Year

Traditional OPEX 500 \$/MW per Year

Data sourced from SAKAKA 300MW projects

Traditional I-V Testing



Onsite
inspection

Loss
of Yields

Manual
Analysis & Reporting

Smart I-V Curve Diagnosis



Online
inspection

No Loss
of Yields

Auto
Reporting

Malaysia Asia Meranti LSSPV Plant 30MW



ASIA MERANTI SDN. BHD. (093243-M)
 Lot 6298, Jalan Taiping, 34200 Parit Buntar, Perak, Malaysia.
 Tel: 05-717 6331, 717 6332 Fax: 05-717 6099
 Email: asiameranti@gmail.com

Date : 10th Feb 2021

Dear Huawei Team,

Recommendations for Exceptional Service and Outstanding Product Capability

- LSSPV Plant of 10MWac at Daerah Larut & Matang, Perak
- LSSPV Plant of 10MWac at Daerah Kampar, Perak
- LSSPV Plant of 10MWac at Daerah Kinta, Perak

We thank you for your service and great support in the implementation our LSS plants.

Since the commissioning of our 3 facilities in 2019Q4, the Huawei Inverters installed in our facilities have been running smoothly.

The Smart I-V Curve function has also helped us tremendously in maintaining the efficiency of our facilities. The ability to perform diagnostics on PV module arrays at the string level remotely have saved us more than 2000 man-hours in O&M activities. On top of that, being able to identify and attend to the underperforming PV arrays early have allowed us to recover more than RM7,400.00 in potential revenue loss across all 3 facilities.

We also would like to express our gratitude to Mr. James Lee and Mr. Farhan b. Zaini for their professionalism and continuous assistance in providing us with technical support throughout the installation and operation of our facilities.

Sincerely,
 For and on behalf of
 Asia Meranti Sdn Bhd


Zack Yong
 Director

The **Smart I-V Curve function** helped us tremendously in **maintaining the efficiency** of our facilities. The ability to perform diagnostics on PV module arrays at the string level remotely **have saved us more than 2000 man-hours in O&M activities**. On top of that, being able to **identify and attend to the underperforming PV arrays** early have allowed us to **recover more than RM7,400.00** yearly in potential **revenue loss** across all 3 facilities.


Huawei Components

*SUN2000-185KTL-H1; STS-6000K-H1; SACU2000B; FusionSolar
 Smart PV Management System; Smart I-V Curve Diagnosis*


Total Capacity of 30MW commissioned in Y2019



The Design of string Inverter Cooling System Has Defects



HW	others	Comments
4 pcs fans	6 pcs fans	Others: more fans, higher power consumption
High-density Ventilation board	No filter	Others: foreign matters cause fans failure
Side air outlet	Top-to-Bottom Straight air outlet	Others: Rainwater enters and causes corrosion
Self-clean function	No	HW: self-clean after power-on



Other string site testing:
Noise decibel 83dB (1m distance)

Hazard Analysis:

- ✗ High fan speed, mechanical vibration affects the reliability of inverter components;
- ✗ It shows that the other solution has high power loss and heat generation, and the long-term reliability of the product is doubtful;
- ✗ 6 fans consume over 200W power;
- ✗ Noise pollution, endangering human health


Smart Grid-connection supporting stable operation in all-scenario grid scenarios

Robust Operation under All Grid Scenario




Support Weak Grid SCR=1.1 (full output)

Operation Stability in weak grid
Smart PV Controller maintains stable operation, Other inverter **shuts down for protection due to oscillation**




Active THD inhibition THDi<1%


Harmonic injection in weak grid



Digital Simulation
Grid code simulation modeling



Semi-physical Simulation
'Hardware in the Loop'




Real Testing
Grid simulation test in the lab, Onsite testing




Success Case: Huawei Smart PV Fully Compliance with World's Strictest Grid Code

Huawei Smart PV: Unique string solution fully compliance with Australian new strict grid code




Success Case: Huawei Smart PV stable operation in weak grid



Apr 4th 2020, 09:32:26, Massive shutdown.

Stage I 100MW project contingency event recording...



- 35 out of 140 inverters shutdown and damaged.
- Whole plant shuts down for 2 weeks (3% yield loss) ..
- Replacement of control PCB of all inverters ... does not guarantee no recurring.



Meanwhile.. **Huawei inverter log:**
Detected the fault accurately and rode through the fault.

File	Frs	Time	ID	Event	LVRT	IVRT	Grid_AB	Grid_BC	Grid_CA	Grid_PosSeq	Grid_NegSeq	Id_Ref	Iq_Ref
0	A	0...	2020/4/4 9:38:54	INV_VRT_INFO_LOG_VRT	1	0	5062	5042	5047	3343	627	1128	65352
*													

Reliability is Huawei DNA, strictly tested by GCTC above industry level

Huawei Global Compliance & Testing Center (GCTC) is recognized by international authoritative organizations.



Huawei GCTC



K3 Lab in Shenzhen



GCTC in Shanghai



GCTC in Shenzhen




K3 Lab in Shenzhen



THB Test
85°C
Humidity: 85%-90%



High Temperature
Resistance Test
Waterproof Test



HALT
-60 °C ~ 110 °C
5-time Cycle Test



Dustproof Test
24-Hour/Dirt Retention
48-Hour/Humidity



Salt Mist
Reliability Test
Corrosion resistance



Rocket triggered Lightning
at Guangdong

1400+ Test Cases

21 Specific Tests

Automatic production line Guaranteed unified and long-term product reliability

Fully-automatic Product Line

Product Line Overview



Logistics Center



Strict Online Quality Check

Dielectric Test



Burn-in Test



Gas Leakage Test



Barcode Check



03

SUN2000 330KTL Block Design

Bill of material



	Equipment	Type	number
1	Inverter	SUN2000-330KTL-H2	30
2	STS	Jupiter-9000KTL-H0	1
3	SACU	SACU2000D	1

SUN2000 330KTL H2



Rated output power @ 50: 275 kVA

Maximum output power: 330 kVA (30°C)

Output voltage: 800 V AC

Input operating voltage range: 500 - 1500 V

No. of MPPT: 6 Nos

Maximum input current: 65A per MPPT

Efficiency: 99.0% maximum

Weight: <108 kg

Dimensions: 1048 x 732 x 395 mm

SACU2000D Parameters



Integrated with data acquisition unit
: SmartLogger3000

Operating temperature: -40°C ~ +60°C

Operating Voltage (AC) : 100 V ~ 240 V, L / N (L)+ PE


Dimension : 640 x 770 x 315 mm

Weight: 27.6 kg

installation: Brackets, Holding bars, Wall hanging

Detailed info please refer to user manual and quick guide

Communication and monitoring system network




SUN2000-330KTL-H2

- One SACU/SmartLogger3000 can manage up to 80 inverters
- The optical ring network formed by the SmartLogger can connect to a maximum of 15 SACUs/SmartLogger.
- Check whether the interfaces and protocols match when the SmartLogger connects to other third party devices in the southbound direction.




2P Fixed Tilt MMS + Bifacial Module: Sample block

北
NORTH



Inverter model	SUN2000-330KTL-H2
PV module power (Wp)	545
#Module in series	29
Inverter nominal power (kW)	275
String per inverter	21
#Inverter	30
DC capacity (kWp)	9957
AC capacity (kWac)	8250
DC/AC ratio	1.21
Pitch (m)	10

1P Horizontal Single-axis Tracker + Bifacial Module: Sample block layout



Inverter model	SUN2000-330KTL-H2
PV module power (Wp)	545
#Module in series	29
Inverter nominal power (kW)	275
String per inverter	21
#Inverter	30
DC capacity (kWp)	9957
AC capacity (kWac)	8250
DC/AC ratio	1.21
Pitch (m)	5

Qinghai Santara utility-scale PV project

Huawei smart PV solution

Contributes to successful grid connection of the world's largest single-site PV station

The total AC capacity is **2.2 GW**, including 1.6 GW AC from Huawei smart string inverters.

Smart O&M – Smart I-V curve diagnosis 4.0, taking only 20 mins to scan a 100MW PV plant

Grid forming – Weak grid support (SCR down to 1.2), supporting stable operation in all-scenario grid scenarios

Safe & reliable – TUV verified: Cumulative failure rate < 0.6‰

Inverter SUN2000-175KTL-H0, Grid connection time: September 30, 2020

* The world's first ultra-high voltage power line that delivers 100% renewable energy over long distances

* The world's largest single-site renewable energy project with the shortest construction time

